

Glass-Foil-Module: SOLARWATT BLUE 60P



Made in Dresden

- SOLARWATT solar modules are exclusively produced in Germany.
- 100 % protection against PID
- 260 Wp – 270 Wp (100 % plus sorting)

Standard Warranty

- 10 year product warranty
- Linear performance warranty covering 25 years

Extended warranty by purchasing SOLARWATT Full Coverage insurance

- 12 year product warranty
- All risk insurance

According to the „Special warranty conditions for SOLARWATT solar modules“



*Test requirements: see rear of data sheet

SOLARWATT Service



SOLARWATT Full Coverage

optional (up to 1000 kWp)



Take-back service

as per Delivery Terms for SOLARWATT Solar Modules



Country of origin

Quality made in Germany

Product Quality



long-lasting



innovative



resistant against ammonia



resilient



low-glare



resistant against hail



high-yield



safe



resistant against salt mist



SOLARWATT GmbH | Maria-Reiche-Str. 2a | 01109 Dresden | Germany
Tel. +49 351 8895-333 | Fax +49 351 8895-111 | www.solarwatt.de
Certified acc. to DIN EN ISO 9001 and 14001 | BS OHSAS 18001:2007



Product-warranty

as per Special Warranty Conditions for SOLARWATT Solar Modules



Performance-warranty

as per Special Warranty Conditions for SOLARWATT Solar Modules

SOLARWATT Expert Installer

Technical Data Glass-Foil-Module: SOLARWATT BLUE 60P

Dimensions	
LxWxH	1680 ^{±2} x 990 ^{±2} x 40 ^{±0.3} mm
Connection technology	Cables 2 x 1,0 m / 4 mm ² , PV4-Connector
Weight	appr. 19 kg

Electrical Data (STC)			
STC: Standard Test Conditions: Irradiation intensity 1000 W/m ² , spectral distribution AM 1,5 Temperature 25±2 °C, in accordance to EN 60904-3			
Nominal power P_N	260 Wp	265 Wp	270 Wp
Nominal voltage U_{MPP}	30,9 V	31,1 V	31,2 V
Nominal current I_{MPP}	8,50 A	8,61 A	8,73 A
Open circuit voltage U_{OC}	37,9 V	38,1 V	38,2 V
Short circuit current I_{SC}	9,00 A	9,11 A	9,23 A
I_R[*]	20 A		
Measurement tolerance in reference to P _{max} ±5%; Reduction of module efficiency when irradiance is reduced from 1000 W/m ² to 200 W/m ² (at 25 °C): 4 ± 2% (relative) / -0,6 ± 0,3% (absolute). * Reverse-current power rating: Operating modules with an external power source is only permissible if using a phase fuse with a tripping current of ≤ 20 A.			

Electrical Data (NOCT)			
NOCT: Normal Operation Cell Temperature: Irradiation intensity 800 W/m ² , AM 1,5 Temperature 20 °C, Wind speed 1 m/s, open circuit operation			
Nominal power P_N	191 W	195 W	198 W
Nominal voltage U_{MPP}	28,6 V	28,7 V	28,8 V
Nominal circuit voltage U_{OC}	35,6 V	35,7 V	35,9 V
Short circuit current I_{SC}	7,27 A	7,36 A	7,46 A

General Data	
Module technology	Glass-Foil-Laminate; aluminium frame
Covering material	Tempered solar glass with anti-reflective finish, 3,2 mm
Encapsulation	EVA-solar cells-EVA
Backing material	Multi-layer composite film, white
Solar cells	60 polycrystalline solar cells
Cell dimensions	156 x 156 mm
Bypass diodes	3
Application class	A (acc. to IEC 61730)
Max. system voltage	1000 V
Mechanical Ratings as per IEC 61215 Ed.2	Suction load up to 2400 Pa Applied load up to 5400 Pa
Approved stress load as per SOLARWATT Installation Instructions	Applied load up to 3500 Pa (when installed crosswise ¹⁾) Test condition: sliding load of 5400 Pa (conditions take into account safety factors for snow overhang and ice load per Eurocode 1.) ¹⁾ Please refer to the specifications in the installation instructions.
Qualifications	IEC 61215 Ed.2 IEC 61730 (including Protection Class II)

Characteristic Lines	
Voltage characteristic line at different temperatures and irradiances	
Performance class 265 Wp SOLARWATT BLUE 60P	

Thermal Properties	
	SOLARWATT BLUE 60P
Operating temperature range	-40 ... +85 °C
Ambient temperature range	-40 ... +45 °C
Temperature coefficient P_N	-0,41%/K
Temperature coefficient U_{OC}	-0,31%/K
Temperature coefficient I_{SC}	0,05%/K
NOCT	45 °C